

Fomax F9105 Panel PC



◆ Specifications

Model		Fomax F9105	
Basic Configuration			
CPU	Intel® Core™ i3 2.1GHz, 3M Cache, 64 Bit, Dual-Core (Standard)	Intel® Core™ i3/i5/i7/Pentium®/Celeron® Mobile Processor, PGA988 Socket (Option)	Intel® QM77
	Chipset		
Memory	2GB DDR3 SODIMM (2×SODIMM), Max. 16GB		
Storage	1×500GB, With 24×7 operation (Standard) HDD (2.5"), SSD (Option)		
Expansion Slots	1×PCI-Ex16, 1×Mini-PCIe (full-size)		
I/O Interface	Standard: 2×RS-232/422/485, 3×RS-232 (rear); 1×RS-232 (Internal, optional external)		
	Standard: 4×USB 2.0, 2×USB 3.0 (rear); 4×USB 2.0, 2×USB 3.0 (Internal, optional external)		
Video Memory	2×SATA 2.0, 2×SATA 3.0 (support RAID 0/1/5/10)		
	2×10/100/1000M 1×VGA, 1×HDMI, 1×Display-Port 1×Line in, 1×Line Out, 1×Mic 1×PS/2 Keyboard & Mouse (share with Y-Cable) Power Switch, Power LED, Power Interface		
Drivers		Option External USB DVD-ROM or DVD-RW	
Monitoring			
Watchdog	0~255 Sec		
Displays			
Type	19" SXGA TFT LCD		
Resolution	1280×1024		
Brightness	250cd/m ²		
Contrast Ratio	1000:1		
Viewing Angle	170° (H), 160° (V)		
Backlight	LED		
Touchscreen	5-wire resistive type (Standard)		
Power			
Power Input	100~240VAC		
Mechanical Specifications			
Cooling	Active with fan		
Construction	Aluminum Front Panel & Stainless Steel Panel, VESA		
Mounting			
Dimensions (W×H×D)	464mm×375mm×90mm		
Cutout Size (W×H)	403mm×331mm		
Weight	8.7kg		
Environmental			
Operating Temperature	0~50°C		
Storage Temperature	-0~70°C		
Relative Humidity	10~85% (non-condensing)		
IP Rating	IP65 compliant front panel		
Certification	FCC, CE		



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008