

## Fomax S1502 Flat Panel PC



### ◆ Specifications

Model		Fomax S1502	
<b>Basic Configuration</b>			
CPU	Onboard Intel® Celeron® Processor J1900 2.0GHz, up to 2.42GHz, 2M Cache, 64 Bit, Quad-Core		
Memory	4GB DDR3L SODIMM (1×SODIMM), Max. 8GB		
Storage	1×500GB, With 24×7 operation (Standard) HDD (2.5"), SSD, mSATA (Option)		
Expansion Slots	2×Mini-PCle (full-size, one share with mSATA), 1×Sim 4×RS-232 (COM1~4), 1×RS-232/485 (COM6) 4×USB 2.0		
I/O Interface	1×SATA 2.0, 1×mSATA 2×10/100/1000M 1×VGA, 1×HDMI Power Switch, Power LED, Power Interface		
Video Memory	On board, DVMT		
<b>Drivers</b>			
Option	External USB DVD-ROM or DVD-RW		
<b>Monitoring</b>			
Watchdog	0~255 Sec		
<b>Displays</b>			
Type	15" XGA TFT LCD		
Resolution	1024×768		
Brightness	420cd/m <sup>2</sup>		
Contrast Ratio	800:1		
Viewing Angle	160° (H), 160° (V)		
Backlight	LED		
Touchscreen	5-wire resistive type (Standard)		
<b>Power</b>			
Power Input	12VDC Input (2 Port terminal), with power adapter		
<b>Mechanical Specifications</b>			
Cooling	Fanless		
Construction	Aluminum Front Panel & Steel Panel, VESA		
Mounting			
Dimensions (W×H×D)	369mm×301mm×85mm		
Cutout Size (W×H)	353mm×283mm		
<b>Environmental</b>			
Operating Temperature	0~50°C		
Storage Temperature	-20~70°C		
Relative Humidity	10~85% (non-condensing)		
IP Rating	IP65 compliant front panel		
Certification	FCC, CE		



**Shanghai Nematron Technology Co., Ltd.**

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008