

SE403 Rackmount Server



◆ Specifications

Model	SE403
CPU	
Default Configuration	Intel® Xeon® 1.8GHz, 10M Cache, 64 Bit, Quad-Core
Option	Intel® Xeon® E5-1600/E5-2600 CPU series (LGA2011 Socket)
Chipset	
Southbridge	Intel® C602
Memory	
Default Configuration	2GB REG ECC DDR3 (8×DIMM, Support dual channel)
Max.	256GB
Slots	
PCI-Ex16	2
PCI-Ex8	2 (w/ x4 Link)
PCI	1
Storage	
Default Configuration	1×1TB (64M Cache, With 24×7 operation)
Option	HDD(3.5"), SSD
Driver	
Default Configuration	DVD-ROM
Option	DVD-RW
I/O Interface	
Serial Port	2×RS-232 (internal lead to external)
USB	Standard: 10×USB 2.0 (2 front, 8 rear), 2×USB 3.0 (rear); 4×USB 2.0, 2×USB 3.0 (internal lead to external)
SATA	4×SATA 2.0, 4×I-SATA 2.0, 2×I-SATA 3.0 (support RAID0/1/5/10)
Ethernet	2×10/100/1000M (Intel® Network Chip)
Audio	1×Line-in, 1×Line-out, 1×Mic-in, 1×

K&M Port	Center/LFE-out, 1×Surround-out, 1×S/P DIF Out 1×PS/2 Keyboard & Mouse (share with Y-Cable)
Display	
Onboard display interface	No on-board display, need to insert graphics card
Video Port	1×VGA, 1×DVI-D, 1×HDMI
Video Memory	1GB (Plug-in PCI-Ex16 graphics card)
Monitoring	
Watchdog	0~255 Sec
Power	
Default Configuration	ATX PS2 power
Option	Redundant power supply
Others	
Keyboard & Mouse	Standard: PS/2 Keyboard & 3D USB Mouse
Environmental	
Operating Temperature	0~50°C
Storage Temperature	-20~70°C
Relative Humidity	5~95% (non-condensing)
Vibration	1.5g
Shock	10g
MTBF	50,000 hrs
Dimensions (W×H×D)	483mm×177mm×510mm
Chassis	Black panel, 2×12cm ball bearing fans, 93CFM
Certification	FCC, CE



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008