

Smart T6002 Emedded IPC



◆ Specifications

Model	Smart T6002		Audio	1×Line-Out, 1×Mic
CPU	Onboard Intel® Core™ i5-4300U 1.9GHz, up to 2.9GHz, 3M Cache, Dual-Core		K&M Port	USB
Default Configuration	4GB DDR3L SODIMM (2×SODIMM), Max. 16GB		Display	
Memory	2 (Extensible special modules)		Video Port	1×HDMI, 1×DisplayPort
Default Configuration	2×full-size (one share with mSATA)		Video Memory	On board, DVMT
Slots	1		Monitoring	
PCI-Ex1	1		Watchdog	0~255 Sec
Mini-PCle	1		Power	
Sim	1		Default Configuration	DC12V Input (Interface can be locked), with 90~240VAC, 12VDC/5A/60W power adapter
Storage	1×500GB (With 24×7 operation)		Mechanical Specifications	
Default Configuration	HDD (2.5"), SSD, mSATA		Cooling	Fanless
I/O Interface	2×RS-232 (rear); Option increase: 4 or 8×RS-232/422/485 (front)		Construction	Aluminum & Steel
Serial Port (DB9)	2×USB 2.0, 2×USB 3.0 (rear)		Mounting	Desktop, Wallmount
USB	2×SATA 2.0, 1×mSATA		Dimensions (W×H×D)	185mm×60mm×175mm
SATA	2×10/100/1000M (rear); Option increase: 4 or 8×10/100/1000M (front)		Weight	2.4kg (w/o power adapter)
LAN	8-Bit		Environmental	
GPIO			Operating Temperature	0~60℃
			Storage Temperature	-10~70℃
			Relative Humidity	10~90% (non-condensing)
			Certification	CE, FCC



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008