

## Smart T6007 Emedded IPC



### ◆ Specifications

<b>Model</b>	Smart T6007
<b>CPU</b>	
<b>Default Configuration</b>	Onboard Intel® Core™ i5-7200U 2.5GHz, up to 3.1GHz, 3M Cache, 64 Bit, Dual-Core or Onboard Intel® Core™ i7-6500U 2.5GHz, up to 3.1GHz, 4M Cache, 64 Bit, Dual-Core
<b>Memory</b>	
<b>Default Configuration</b>	4GB DDR4 SODIMM (2×SODIMM), Max. 32GB
<b>Slots</b>	
<b>Mini-PCIe</b>	1×full-size(share with mSATA), 1×half-size
<b>Storage</b>	
<b>Default Configuration</b>	1×500GB (With 24×7 operation)
<b>Option</b>	HDD (2.5"), SSD, mSATA
<b>I/O Interface</b>	
<b>Serial Port</b>	Standard: 1×RS-232/422/485, 1×RS-232 (front) Option: 2×RS-232 (front), 1×RS-232 (rear)
<b>USB</b>	4×USB 2.0 (2 front, 2 rear), 4×USB 3.0 (rear)
<b>SATA</b>	1×SATA 3.0, 1×mSATA
<b>LAN</b>	2×10/100/1000M (rear)

<b>GPIO</b>	8-Bit (internal optional)
<b>Audio</b>	1×Line-Out, 1×Mic
<b>K&amp;M Port</b>	USB
<b>Display</b>	
<b>Video Port</b>	Standard: 1×HDMI, 1×DisplayPort
<b>Video Memory</b>	On board, DVMT
<b>Monitoring</b>	
<b>Watchdog</b>	0~255 Sec
<b>Power</b>	
<b>Default Configuration</b>	DC12V, with 90~240VAC, 12VDC/5A/60W power adapter
<b>Mechanical Specifications</b>	
<b>Cooling</b>	Fanless
<b>Construction</b>	Aluminum & Steel
<b>Mounting</b>	Desktop, Wallmount
<b>Dimensions (W×H×D)</b>	193mm×62mm×142.4mm
<b>Weight</b>	2.2kg (w/o power adapter)
<b>Environmental</b>	
<b>Operating Temperature</b>	0~50℃
<b>Storage Temperature</b>	-10~70℃
<b>Relative Humidity</b>	10~90% (non-condensing)
<b>Certification</b>	CE, FCC



**Shanghai Nematron Technology Co., Ltd.**

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008