

Smart T6310 Emedded IPC



◆ Specifications

Model	Smart T6310		GPIO	24 Bit
CPU			Audio	1 × Line-Out, 1 × Mic
Default Configuration	Onboard Intel® Core™ i3 2.7GHz, 4M Cache, 64 Bit, Dual-Core		K&M Port	1 × PS/2 Keyboard & Mouse (share with Y-Cable)
Option	6th Intel® Core™ i3/i5/i7/Pentium®/Celeron® Processor		Display	
Chipset			Video Port	1 × VGA, 1 × HDMI
Southbridge	Intel® HM170/QM170		Video Memory	On board, DVMT
Memory			Monitoring	
Default Configuration	4GB DDR4 SODIMM (2 × SODIMM), Max. 32GB		Watchdog	0 ~ 255 Sec
Slots			Power	
PCI or PCIe	2 × PCI, 1 × PCI-Ex4		Default Configuration	DC-in: 9 ~ 36VDC
Mini-PCIe	1 × Full-size (share with mSATA)		Option	120W / 150W power adapter
Storage			Mechanical Specifications	
Default Configuration	1 × 500GB (With 24 × 7 operation)		Cooling	Fanless
Option	CF, HDD (2.5"), SSD, mSATA		Construction	Aluminum & Steel
I/O Interface			Mounting	Desktop, Wallmount
Serial Port	Standard: 2 × RS-232/422/485 (COM1-2), 3 × RS-232 (COM3-10, with 1 to 8 serial cable); 4 × RS-232 (internal optional)		Dimensions (W × H × D)	210mm × 155mm × 240mm
Parallel Port	1 (internal optional)		Environmental	
USB	2 × USB 2.0, 4 × USB 3.0		Operating Temperature	-20 ~ 70 °C
SATA	2 × SATA 3.0, 1 × mSATA, 1 × CF		Storage Temperature	-45 ~ 85 °C
LAN	6 × 10/100/1000M		Relative Humidity	5 ~ 95% (non-condensing)
			Certification	FCC, CE



Shanghai Nematron Technology Co., Ltd.

245 Xinjun Ring Road, Suite D302 Caohejing Pujiang Hi-Tech Park, Shanghai 201114, China

Tel: +86 21 5109 6600

Fax: +86 21 5426 3008